



## CURIX 60 PROCESSOR

High-quality images with  
table-top processor



### Maximum performance on minimum footprint

The Curix 60 is a table-top processor equipped with highly performant technology. It can be easily fitted into a small space, still guaranteeing maximum image quality. The Curix 60 is ideal for low-volume radiology and provides consistent, high-quality processing of film with a maximum width of 36 cm. Furthermore, the Curix 60 may serve as an ideal back-up for your regular processor.

### Superior performance

Thanks to the infrared dryer, superior drying performance is obtained together with low power consumption and a low noise level. To ensure consistent high-quality images, the

bath temperature is controlled electronically.

### Compact and time-saving

Due to the clever location of the replenisher tanks, the position of the film delivery slot and the boomerang system, which brings the processed film on top of the processor, its floor space is minimal and access is easy. The exclusive Curix 60 light-tight cover design allows you to leave the darkroom after approx. 15 seconds. You don't need to wait until the film completely entered the processor.

### Kind to your working environment

When you open the Curix 60 processor, you will notice that both the chemical tanks and the rollers are covered. Your working environment will not be disturbed by chemical fumes any more.

### Optimum replenishment

On the whole, the flow of replenishment is controlled by scanning the film surface. When the Curix 60 is used at irregular intervals, half the contents of the developing tray can be replaced by simply pressing the 'Optimising key', i.e. the black key in the middle.

# Curix 60

## Technical data

<b>Dimensions (l x w x h)</b> 80 x 65 x 38 cm (31.5 x 25.5 x 15 in) Note: length with feeder tray is 94 cm (37 in)	<b>Film sizes</b> Min. size: 10 x 10 cm (diagonally) Max. width: 36 cm	<b>Automatic stand-by mode</b>  <b>'Optimising key' for replenishment</b>
<b>Weight</b> Empty: 60 kg (132 lbs) With replenisher bottles: 69 kg (152 lbs)	<b>Film transport speed</b> 28.5 cm/min	<b>Power supply</b> 50 Hz, 230 V, 1500 W max. 50 Hz, 200 V, 1500 W max. 60 Hz, 100 V, 1500 W max.
<b>Tray capacity</b> Developer tank: 0.9 l (0.2 gal) Fixer tank: 0.9 l Wash tank: 0.9 l Replenisher bottles: 2.5 l (0.7 gal)	<b>Drying system</b> Infrared	<b>Warming-up time</b> 7 min
<b>Capacity</b> 60 films/hour	<b>Standard equipment</b> Processor + set of 3 replenisher bottles	<b>Safety</b> This processor complies with the VDE, UL and CSA safety regulations and with the VDE regulations on radio interference suppression. The non-return water connection complies with the DIN standard for connection to drinking water systems of the DVGW. The unit is supplied with the GS label.
<b>Processing cycle</b> 3 min	<b>Accessories</b> Water supply connection Light-tight cover Processor stand Set of three replenisher bottles of 2.5 l (3 x 0.66 gal)	

Not all options/products mentioned in this data sheet are available in all countries. In case of doubt, please contact your Agfa Sales Organisation.

The data in this publication are for illustration purposes only and do not necessarily represent standards or specifications which must be met by Agfa. Characteristics of the products described in this publication can be changed at any time without notice.

Curix is a trademark of Agfa-Gevaert N.V., Belgium.  
 Agfa and the Agfa-Rhombus are trademarks of Agfa-Gevaert AG, Germany.

Printed in Belgium  
 Published by Agfa-Gevaert N.V.,  
 B-2640 Mortsel-Belgium  
 NEKHL GB 00199812 V03

Agfa-Gevaert has been awarded the ISO 9001 Certificate by Lloyd's Register Quality Assurance for the design, development, procurement and/or production, marketing and servicing of imaging and communication systems for medical applications. A high consistency of products is thereby provided.

